

GRAIN TIPPER



CRYSTEEL

- *Free-flow unloading.*
- *Crossmemberless understructure is strong, self-cleaning.*
- *10 body lengths from 15 through 26 feet.*
- *Stingray hoists provide a perfect combination of power and function.*



Building the World's Best Truck Bodies & Hoists

Grain Tipper Specifications

| Inside Body Length in feet | | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 24 | 26 |
|----------------------------|--|------|------|------|------|------|------|------|------|------|------|
| 46" Sides | Bushel Capacity 96" Body Width | 365 | 389 | 412 | 436 | 460 | 484 | 508 | 532 | 580 | 627 |
| | Bushel Capacity 102" Body Width | 388 | 414 | 439 | 464 | 490 | 515 | 541 | 566 | 617 | 668 |
| | Approx Weight in lbs 96" Body Width | 2300 | 2412 | 2474 | 2636 | 2748 | 2860 | 2972 | 3084 | 3308 | 3532 |
| 60" Sides | Bushel Capacity 96" Body Width | 475 | 507 | 538 | 569 | 600 | 631 | 662 | 693 | 756 | 818 |
| | Bushel Capacity 102" Body Width | 506 | 539 | 572 | 606 | 639 | 672 | 705 | 738 | 804 | 871 |
| | Approx Weight in lbs 96" Body Width | 2660 | 2788 | 2916 | 3044 | 3172 | 3300 | 3428 | 3556 | 3812 | 4068 |
| 14" Tip Tops | Add'l Bushel Capacity 96" Body Width | 112 | 119 | 127 | 134 | 142 | 149 | 157 | 164 | 179 | 194 |
| | Add'l Bushel Capacity 102" Body Width | 119 | 127 | 135 | 143 | 150 | 158 | 166 | 174 | 190 | 206 |

CAUTION: The combined weights of truck, body, hoist and load must not exceed the truck's Gross Vehicle Weight rating. Capacities based on water-level load, 50° dump angle, and includes body weight. Some equipment shown may be optional. Specifications subject to change.

Standard Features



Standard 3-door rear gate with center grain chute.

Smooth Surfaces

Inside, Crysteel Grain Tipper are designed with smooth, snag-free sidewalls and steel floors to prevent bridging of loads.

Outside, the smooth sidewalls improve air flow and are great for graphics.

Below, the understructure contains no crossmembers resulting in smooth self-cleaning surfaces that are strong, but without unnecessary weight.

Crysteel Grain Tipper are built with materials and design features that offer years of performance and value:

- Unitized all-welded construction
- High strength 50,000 psi yield steel
- Tubular longbeams, side rails and top rail
- Swing-out 3-section rear gate with rubber seals and large 12" x 24" grain gate in center door
- Rubber-mounted stop, turn, and clearance lights
- 46" side height
- 96" body width

Optional Features

- 60" side height
- 102" body width
- 7 gauge AR floor, ideal for forklift loading
- Crysteel Stingray hoists
- 14" high Tip Tops can be used two-high on 46" sides

Rear Gate Options

- Mesh rear gate with automatic opener/closer
- 2-piece barn door
- Combo beet/grain
- Sweet Corn gate
- Hydraulic gate
- Center chute available on all except sweet corn or beet



New! Optional hydraulic tailgate.



Optional mesh rear gate.



CRYSTEEL MANUFACTURING, INC.

52182 Ember Rd • Lake Crystal, MN • 56055 & 1902 Rt. 57 South • Fulton, NY • 13069

1-800-533-0494 • 1-507-726-2728 • FAX 1-507-726-2559 • Internet <http://www.crysteel.com> • e-mail crysteel@crysteel.com

Sold by: