



Behind The Cab Prewet Tank Kit

Standard System Includes:

- Dual 120 Gallon Poly Tanks
 - 6"x8"x4" sump area
 - .350" minimum wall thickness
 - 10" fillwell, lid with lanyard
 - (9) 1.25" FNPT molded in ports
 - (4) tube type tank baffles
- Powder coated mild steel framework
- Four (4) 3" wide nylon straps with stainless steel draw bolts
- Two (2) formed mounting brackets to attach to chassis frame rail
- Overall dimensions 78"L x 17.5"W x 64" High
- Requires only 20" of open space behind the cab



*Optional Corrosion-Resistant
Stainless Steel Frame and
Mounts Shown*

Can Be Combined With Most of Our Pre-Wet Systems

- LDS-333 Electric Driven Liquid Dispensing System
- Activator Electric Driven Liquid Dispensing System
- LDS-455 Hydraulic Driven Liquid Dispensing System
- Versa-Coat Deluxe Hydraulic Driven Liquid Dispensing System
- Closed Loop Electric Driven Liquid Dispensing System
- Closed Loop Hydraulic Driven Liquid Dispensing System



*Recommended clearance between
cab and tank 2" minimum.*

Optional Equipment

- Corrosion-resistant stainless steel frame and mounts
- Bulk fill and cross over kit
- Flusher kit



Manufactured by:

Monroe Snow & Ice Control
A Division of Monroe Truck Equipment
1051 W. 7th Street
Monroe, Wisconsin 53566
800-880-0109 • Fax 608-328-8390 • Website: www.monroetruck.com

Distributed by: