



# Double Function Wing



- All Hydraulically Operated- No Cables
- Single Adjustable Spring Cushioned Push Arm with Safety Shear Pin on 8' and 9' Wings. Double Push Arms on 10', 11' and 12' Wings
- Rugged Moldboard Construction
- 100% Welded Moldboard
- One Piece 1/2" Moldboard Reinforcement Ribs
- Rear Push Frame Mounted Above Frame for Increased Ground to Frame Clearance
- No Additional Cab to Body Spacing Required for Rear Push Arm Frame
- Free Float to Follow Contour of Road or Shoulder

The Monroe Double Function Patrol Wing is a multi-function wing that is capable of patrolling snow to widen shoulders or perform limited benching capabilities. The Double Function Wing is operated by hydraulic cylinders for positive activation of the wing. The operator has the ability to independently control the toe or heel of the wing. Another feature is the built in mechanical float to allow the wing to follow the contour of the plowing surface. The mounting of this wing usually requires no modification to the exhaust system, no additional cab to body spacing, no drivetrain interference and a rear mount that is located above the frame for an unobstructed ground to frame clearance. A Monroe Wing will increase your plow clearing capacity, increase operator efficiency, and reduce equipment road mile usage.

Two 4-way (double acting) valves are required to operate this unit • All moldboards are shotblasted and powder coated Urethane Orange

## Specifications

	DFPW-8	DFPW-9	DFPW-10	DFPW-11	DFPW-12
Overall Moldboard Length	104"	116"	128"	140"	152"
Cutting Edge Length	8'	9'	10'	11'	12'
Height of Moldboard at Nose	29"	29"	29"	29"	29"
Height of Moldboard at Heel	39"	39"	39"	39"	39"
Moldboard Thickness	3/16"	3/16"	3/16"	3/16"	3/16"
Single Pusharm - Adjustable 4 Positions	STD	STD			
Double Pusharms	OPT	OPT	OPT	OPT	OPT
Inboard Slide Cylinder	3"ID x 24"	3"ID x 24"	3"ID x 24"	3"ID x 24"	3"ID x 24"
Outboard Lift Cylinder	4"ID x 21.75"	4"ID x 21.75"	3"ID x 15"	3"ID x 15"	3"ID x 15"
Weight of Complete Wing Assembly	1620	1690	1870	1985	2050
Weight of Moldboard	700	770	840	720	785
Clearing Width With 90° Push Arm Angle	58"	65"	72"	79"	87"

Specifications subject to change without notice.

## Available Options

Two Piece Torsion Trip Edge  
Carbide Cutting Edge  
Curb Guard  
Power or Manual Slide Front Post  
Full Trip Moldboard

Power Heel Slide  
Power and Manual Tilt Front Hitches  
Dual Pusharms  
Moldboard Wear Shoe  
Decell Cylinder

Custom Cheekplate Hitches  
Left Side or Dual Mount  
Special Paint  
Power Slide Push Arm

Manufactured by:  
**Monroe Snow & Ice Control**  
1051 W. 7th Street • Monroe, WI 53566  
800-880-0109 • 608-329-8105  
608-328-8390 Fax  
Web: [www.monroetruck.com](http://www.monroetruck.com)  
E-mail: [snowandicecontrol@monroetruck.com](mailto:snowandicecontrol@monroetruck.com)

Distributed by: