



Monroe Snow & Ice Control Fixed Angle Rigid Plow



Shown with optional Hasting Hitch.

Features:

- 14" Push Height
- Fixed Angle Pushframe
- Orange Polyurethane Paint Finish
- A Rigid, No-Trip Moldboard
- A C1080 AASHO Top-Punched Cutting Edge

Specifications

| Model OWFA34-71-11 | Model OWFA34-73-12 |
|---|---|
| Intake Height34" | Intake Height34" |
| Discharge Height71" | Discharge Height73" |
| Overall Length of Moldboard168" | Overall Length of Moldboard173" |
| Cutting Edge, 5/8" x 8"132" | Cutting Edge, 1/2" x 6"144" |
| Attack Angle50° | Attack Angle50° |
| Discharge Angle38° | Discharge Angle38° |
| Moldboard Thickness3/16" | Moldboard Thickness3/16" |
| Adjustable Cast Shoes (2)2" x 6" x 16" | Adjustable Cast Shoes (2)2" x 6" x 16" |
| Cutting Width8' 11" | Cutting Width9' 2" |
| Approximate Weight (Plow Only)1450 lbs. | Approximate Weight (Plow Only)2100 lbs. |

Product updates and specifications are subject to change without notice.

Manufactured by:
 Monroe Snow & Ice Control
 1051 W. 7th Street • Monroe, WI 53566
 800-880-0109 • 608-329-8105
 608-328-8390 Fax
 Web Site: www.monroetruck.com
 E-mail: snowandicecontrol@monroetruck.com

Distributed by:

Form FARigid110101