



VERSA-LINE PLATFORM



Fuel fill is recessed in rub rail.

PLATFORM FEATURES

- Constructed of an all steel underframe
- Stake pockets on 24" centers
- Tapered corners
- Weather-resistant, plug-in wiring harness
- Rubber mounted lights to FMVSS specifications



Rubber mounted lights to FMVSS specifications

STAKE BODY FEATURES

- 30" to 40" stake sides
- Stake pockets will accept 2" x 4" lumber
- Slats are made of ribbed steel for strength & durability (*Optional wood slats are available.*)
- Swing gate & hold down latch are standard
- Latch assembly secures corners and sides for less noise & more cargo protection

PLATFORM & STAKE BODY FEATURES

- Floors feature CCA treated water repellent 2" tongue and groove floor boards (*Optional smooth or treadplate steel is available.*)
- 5" x 10 gauge steel side & end rails
- 3" structural channel crossmembers on 12" centers
- Structural channel longsills (6" to 8") are gusseted to every crossmember for strength
- Front & rear crossmembers give added floor strength
- Body is hoist compatible
- Standard sizes available from 7' x 78" to 24' x 96" (*Others upon request*)



AVAILABLE NATION-WIDE
Ship-Thru Code VCB



Versa-Line Platform Body Options

Versa-Line Stake Rack Specifications	
INTERIOR LENGTH	6" less than platform length
INTERIOR WIDTH	96" O.D. x 90" I.D.
SLATS	6" x 16 gauge roll-formed steel or 1" x 6" pine
STAKES	14 gauge roll-formed with liners
FRONT	12 gauge bulkhead with window (standard); stake front optional
REARS	Hinged, swing out
HARDWARE	Spring-loaded, western-style gate locks on swing gate and rears
HOLD DOWN LATCH	Spring-loaded in stake, 1 per section
STANDARD HEIGHTS	40" (GM 3500 and Ford Super Duty); 42" (GM 4500/5500)
SIDE SECTIONS	7'-10' 2-piece sides 12'-20' 3-piece sides/1 swing gate per side 22'-24' 4-piece sides/1 swing gate per side

Versa-Line Contractor Rack Specifications		
	FOLD DOWN STYLE	LIFTOUT STYLE
INTERIOR LENGTH	6" less than platform length	6" less than platform length
INTERIOR WIDTH	96" O.D. x 90" I.D.	87½" O.D x 81¼" I.D. or 96" O.D. x 90" I.D.
SIDES	16" high x 12 gauge formed steel with 14 gauge stakes	14" high x 12 gauge formed steel with 14 gauge stakes
TAILGATE	16" high x 12 gauge formed steel, double-acting	14" high x 12 gauge formed steel, double-acting
FRONT	12 gauge roll-formed bulkhead with window	12 gauge roll-formed bulkhead with window

Versa-Line Grain Rack Specifications			
	42" HIGH	52" HIGH	10" TIP TOP
INTERIOR LENGTH	6" less than platform length	6" less than platform length	6" less than platform length
INTERIOR WIDTH	87½" O.D. x 81¼" I.D. or 96" O.D. x 90" I.D.	90"	90"
PANEL SKINS	16 gauge roll-formed	14 gauge roll-formed	16 gauge roll-formed
STAKES	14 gauge with liners	14 gauge with liners	14 gauge
REAR	2 wings, 39½" x 32" high grain gate, 10" filler panel, bull bar	2 wings, 39½" x 32" high grain gate, 20" filler panel, bull bar	1 piece, full-width

Kneebraced Bulkhead Specifications		
	STANDARD DUTY	HEAVY DUTY
HEIGHT	32", 42" or 52"	42", 52" or 62"
WIDTH	72", 78", 87¼" or 96"	87¼" or 96"
PANEL SKINS	12 gauge formed steel	¾" formed steel
STAKES	14 gauge roll-formed steel with liners	14 gauge roll-formed steel with liners
WINDOW	Full width covered with expanded metal	Full width covered with expanded metal

MARSHFIELD
1601 East 29th St.
Marshfield, WI 54449
715-387-8445
800-882-1900
Fax: 715-387-3952

JOLIET
812 Draper Ave.
Joliet, IL 60432
815-727-3134
800-892-7052
Fax: 815-727-5429

FLINT
2400 Reo Drive
Flint, MI 48507
810-238-4603
877-233-2030
Fax: 810-238-5009

MONROE
1051 West 7th St.
Monroe, WI 53566
608-328-8127
800-356-8134
Fax: 608-328-4278

GREEN BAY
1151 W. Main Avenue
De Pere, WI 54115
920-336-8068
800-848-5400
Fax: 920-336-8118

Visit us on the web at www.monroetruck.com